

Appl. No.: 10/709,861
Amdt. Dated: 12/18/2007
Reply to Office action of: 06/29/2007

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claim 1 (currently amended) An ethanol containing gasoline motor fuel additive composition which reduces and modifies combustion chamber deposit formation for the purpose of reducing engine octane requirement increase and allows the use of lower levels of ethanol while retaining engine performance comprising a mixture of: (a) a fuel conditioner component comprising: (i) from about 2 to about 50 weight percent, based upon the total weight of the fuel conditioner component, of a polar oxygenated hydrocarbon having an average molecular weight in the range of about 200 to about 500, an acid number in the range of about 25 to about 175, and a saponification number in the range of about 30 to about 250, and (ii) from about 2 to about 50 weight percent, based upon the total of the fuel conditioner component, of an oxygenated compatibilizing agent preferably having a solubility parameter in the range of about 7.0 to about 14.0 and moderate to strong hydrogen capacity; and (b) ethanol.

Claim 2 (original) The ethanol containing motor fuel additive composition according to Claim 1, allowing the ethanol to be reduced to less than 10 volume percent while maintaining desired engine performance.

Claim 3 (currently amended) The ethanol containing gasoline motor fuel additive composition according to Claim 1, wherein said additive composition is added to the ~~base~~ gasoline motor fuel in an amount of from about 100 ppm to about 1000 ppm.

Claim 4 (currently amended) The ethanol containing gasoline motor fuel additive composition according to Claim 1, wherein said additive composition is added to the ~~base~~

Appl. No.: 10/709,861
 Amdt. Dated: 12/18/2007
 Reply to Office action of: 06/29/2007

gasoline motor fuel containing a detergent in an amount of from about 100 ppm to about 500 ppm.

Claim 5 (currently amended) The ethanol containing gasoline motor fuel additive composition according to Claim 1, wherein said additive composition is added to the ~~base~~ gasoline motor fuel simultaneously with any other additives.

Claim 6 (currently amended) The ethanol containing gasoline motor fuel additive composition according to Claim 1, wherein said additive composition is added to the ~~base~~ gasoline motor fuel after any other additives has been added.

Claim 7 (currently amended) An ethanol containing gasoline motor fuel additive composition which reduces and modifies both fuel intake system and combustion chamber deposit formation for the purpose of reducing engine octane requirement increase and allows the use of lower levels of ~~alkyl-lead ethanol~~ while retaining engine performance comprising a mixture of: (a) from about 5 to about 50 weight percent, based upon the total weight of the components a and b, of a detergent component selected from the group consisting of (i) a reaction product of: (A) a substituted hydrocarbon of the formula



wherein R_1 is a hydrocarbyl radical having a molecular weight in the range of about 150 to about 10,000, and X is selected from the group consisting of halogens, succinic anhydride and succinic dibasic acid, and (B) an amino compound of the formula



wherein Y is O or NR_5 , R_5 being H or a hydrocarbyl radical having 1 - 30 carbon atoms; A is a straight chain or branched chain alkylene radical having 1 - 30 carbon atoms; m has a value in the range of 1 - 15; n has a value in the range of 0 - 6; and R_2 is selected from the group consisting of H, a hydrocarbyl radical having a molecular weight in the

Appl. No.: 10/709,861
 Amdt. Dated: 12/18/2007
 Reply to Office action of: 06/29/2007

range of about 15 to about 10,000, and a homopolymeric or heteropolymeric polyoxyalkylene radical of the formula



wherein R_3 is H or a hydrocarbyl radical having 1 – 30 carbon atoms, Q, T, and Z are polyoxyalkylene moieties having 1 – 6 carbon atoms, a, b and c each have values ranging from 0 – 30, and d has a value in the range of 1 – 50, and (ii) a polybutylamine or polyisobutylamine of the formula



where R_{11} is a polybutyl or polyisobutyl radical derived from isobutene and up to 20% by weight of n-butene and R_{12} and R_{13} are identical or different and are each hydrogen, an aliphatic or aromatic hydrocarbon, a primary or secondary, aromatic or aliphatic aminoalkylene radical or polyaminoalkylene radical, a polyoxyalkylene radical or a heteroaryl or heterocyclyl radical, or, together with the nitrogen atom to which they are bonded, form a ring in which further hetero atoms may be present; and (b) a fuel conditioner component comprising: (i) from about 2 to about 50 weight percent, based upon the total weight of components a and b, of a polar oxygenated hydrocarbon having an average molecular weight in the range of about 200 to about 500, an acid number in the range of about 25 to about 175, and a saponification number in the range of about 30 to about 250, and (ii) from about 2 to about 50 weight percent, based upon the total of components a and b, of an oxygenated compatibilizing agent preferably having a solubility parameter in the range of about 7.0 to about 14.0 and moderate to strong ~~hydrogen capacity~~ hydrogen capacity.

Claim 8 (original) The ethanol containing motor fuel additive composition according to Claim 7, allowing the ethanol to be reduced to less than 10 volume percent while maintaining desired engine performance.

Appl. No.: 10/709,861
Amdt. Dated: 12/18/2007
Reply to Office action of: 06/29/2007

Claim 9 (currently amended) The ethanol containing gasoline motor fuel additive composition according to Claim 7, wherein said additive composition is added to the base gasoline motor fuel in an amount of from about 100 ppm to about 1000 ppm.

Claim 10 (currently amended) The ethanol containing gasoline motor fuel additive composition according to Claim 7, wherein said additive composition is added to the base gasoline motor fuel containing a detergent in an amount of from about 100 ppm to about 500 ppm.